

E-2010 CENTRAL STATION CONTROL

Encoder/Decoder

Control and monitor your siren warning system from a central location. The E-2010 allows the user to issue system activations and collect remote siren status via RF link or landline.

Features Whelen's field proven COMM/STAT™ Command and Status Monitoring protocol, for fast, secure, and reliable communication.

The E-2010 supports all of the features that are available in Whelen's High-Power Voice and Siren product line, from individual Command selection to user programmed command scenarios or Call Keys. With the selection of one Call Key, an operator may prompt the encoder to issue multiple commands.

With the included computer accessory software, you can connect the E-2010 to a PC for Windows® based programming and data archiving. Data is available through an ACCESS® data base.

E-2010 FEATURES

- 4 line by 40 character backlit, LCD display
- 16 "HOT" Call Keys
- 40 Auxiliary Call Keys
- 2 Time-Of-Day Call Key Activations
- 4 Remote Input Call Keys
- Automatic System Polling
- Internal Alarm Tone
- 2 Contact Closure Outputs for Alarms
- Base Radio Interface
- Channel Grant Input for Trunking Radio Systems
- Optional FSK Signaling
- Security Keylock
- Printer Port
- Battery Backup for Time and Date Features
- Rugged, Membrane Keyboard
- Microphone for Public Address E-2010

COMPUTER INTERFACE FEATURES

- CD-ROM and 9 Pin "D" Cable included
- "Windows®" Based Call Key Programming
- Add Call Key Descriptions
- Hard Drive Archive of All Siren Activity
- Selective Printouts for Status by Siren Location or Date

WHELEN
ENGINEERING COMPANY, INC.



E-2010 CENTRAL STATION CONTROL

Specification Data

GENERAL

The E-2010 Central Station Control is configured to make maximum use of Call Keys or preprogrammed scenarios. In addition, commands are grouped into easy to follow categories for Warning Tones, Digital Voice Messages, Direction (if applicable) and Status. A numeric keypad section allows for individual remote siren addressing.

A 4 line by 40 character LCD display shows all Keyboard and Status activity. Command and Status information are also sent to a printer port and a serial communication port for a PC.

All preprogrammed functions are stored in non-volatile memory. Time and date are protected by internal, rechargeable batteries.

A keylock is available to disable the keyboard, but all status information is still active.

COMPUTER REQUIREMENTS

PC with 486DX or Higher CPU
WINDOWS® 95 or 98
CD-ROM Drive
Comm. Port
Hard Disk Space Required: 8 MB

PRINTER OPTION

Optional. 9 pin, dot matrix, 120 CPS, tractor feed, with parallel cable. Designed to be used with an Okidata #184 printer.

COMMUNICATIONS

Transmitter Connection (Typical 1 of 2 transmitters)

Squelch

Push to Talk
(N.O., N.C. contacts)

Transmit Audio

Receive Audio

Channel Grant Active
(for Trunking)

Signaling

DTMF 2 of 8 format. 10 digit transmit. 14-18 digit receive.

Tone Level

Audio level adjustable.

Transmitter Delay

User selectable delay times.

DIMENSIONS

Height: 3"

Width: 17"

Depth: 9"

Weight: 4.5 lbs.

ELECTRICAL

120 VAC, UL listed, wall mount transformer.

ORDERING INFORMATION

E2010

Central Station Control Unit.

E2010R

Central Station Control Unit (Rack Mount).

E2010P

Printer Option for Okidata #184 Printer and Cable.

E2010FSK

FSK Internal Option.

WHELEN®

ENGINEERING COMPANY, INC.

Route 145, Winthrop Road
Chester, Connecticut 06412-0684
(860) 526-9504
1-800-637-4736
Fax: (860) 526-4784
Internet: www.whelen.com

Whelen Engineering Company, Inc.
reserves the right to upgrade its products with
design improvements without notification.
©1999 Whelen Engineering Company, Inc.
Printed in the U.S.A.
121798-10884A